



KOVSMOL, s.r.o.

Sídlo: Družstevná 34, 080 06 Prešov

www.kovsmol.sk

Predajný sklad: Ku Surdoku 1, 080 01 Prešov

tel.: +421 51 77 22 018, fax: +421 51 758 22 61, mobil: +421 905 483 372

Valcované profily krátke: tyče kruhového prierezu


vyrobené z konštrukčných ocelí triedy 11

valcované za tepla

STN 42 5510

DIN 1013 T

TDP: STN 42 0138



menovitý priemer d (mm)	prierez S (mm ²)	teoretická hmotnosť (kg.m ⁻¹)
6	28,3	0,22
7	38,5	0,30
8	50,3	0,40
9	63,6	0,50
10	78,5	0,62
11	95	0,75
12	113	0,89
13	133	1,04
14	154	1,21
15	177	1,39
16	201	1,58
17	227	1,78
18	254	2,00
19	284	2,23
20	314	2,47
21	346	2,72
22	380	2,99
23	415	3,27
24	452	3,56
25	491	3,86
26	531	4,17
27	573	4,50
28	616	4,84
29	661	5,19
30	707	5,56

menovitý priemer d (mm)	prierez S (mm ²)	teoretická hmotnosť (kg.m ⁻¹)
31	755	5,93
32	804	6,32
34	908	7,14
35	962	7,56
36	1018	8,00
37	1075	8,45
38	1134	8,91
39	1195	9,39
40	1257	9,88
42	1385	10,9
44	1521	12,0
45	1590	12,5
46	1662	13,1
47	1735	13,6
48	1810	14,2
50	1963	15,4
52	2124	16,7
55	2376	18,7
56	2463	19,4
57	2552	20,1
58	2642	20,8
60	2827	22,2
62	3019	23,7
63	3117	24,5
65	3318	26,1

menovitý priemer d (mm)	prierez S (mm ²)	teoretická hmotnosť (kg.m ⁻¹)
68	3632	28,5
70	3848	30,2
73	4185	32,9
75	4418	34,7
78	4778	37,6
80	5027	39,5
82	5281	41,5
85	5674	44,6
88	6082	47,8
90	6362	50,0
95	7088	55,7
100	7854	61,7
110	9503	74,7
115	10387	81,6
120	11310	88,9
125	12272	96,5
130	13273	104
140	15394	121
150	17671	139
160	20106	158
170	22698	178
180	25447	200
190	28353	223
200	31416	247
210	34636	272