



KOVSMOL, s.r.o.

Sídlo: Družstevná 34, 080 06 Prešov

www.kovsmol.sk

Predajný sklad: Ku Surdoku 1, 080 01 Prešov

tel.: +421 51 77 22 018, fax: +421 51 758 22 61, mobil: +421 905 483 372


Ťahané profily: tyče kruhového prierezu

vyrobené z ocelí triedy 11

ťahané za studena

medzné úchylky h11 a h12

STN 42 6510, DIN 658, TDP:STN 42 0134



menovitý priemer d (mm)	prierez S (mm ²)	teoretická hmotnosť (kg.m ⁻¹)
4	12,57	0,10
5	19,63	0,15
6	28,27	0,22
7	38,48	0,30
8	50,27	0,40
9	63,62	0,50
10	78,54	0,62
11	95,03	0,75
12	113,10	0,89
13	132,73	1,04
14	153,94	1,21
15	176,71	1,39
16	201,06	1,58
17	226,98	1,78
18	254,47	2,00
19	283,53	2,23
20	314,16	2,47
21	346,36	2,72
22	380,13	2,99
23	415,48	3,27
24	452,39	3,56
25	490,87	3,86
26	530,93	4,17
27	572,55	4,50
28	615,75	4,84
29	660,52	5,19
30	706,86	5,56
31	754,77	5,93
32	804,25	6,32

menovitý priemer d (mm)	prierez S (mm ²)	teoretická hmotnosť (kg.m ⁻¹)
33	855,30	6,72
34	907,92	7,14
35	962,11	7,56
36	1017,88	8,00
38	1134,11	8,91
39	1194,59	9,39
40	1256,64	9,88
42	1385,44	10,89
43	1452,20	11,41
44	1520,53	11,95
45	1590,43	12,50
46	1661,90	13,06
48	1809,56	14,22
50	1963,49	15,43
52	2123,71	16,69
53	2206,18	17,34
54	2290,22	18,00
55	2375,83	18,67
56	2463,01	19,36
60	2827,43	22,22
63	3117,24	24,50
65	3318,30	26,08
70	3848,45	30,25
75	4417,86	34,72
80	5026,54	39,51
85	5674,50	44,60
90	6361,72	50,00
95	7088,21	55,71
100	7853,98	61,73